

The CP-2272E remote control panel features two small high-resolution color LCD displays alongside an array of 72 full color dynamic LCD buttons, all of which are fully programmable. The two LCD displays intelligently interact with the panel's buttons and rotary controls, updating automatically as different operation facilities are selected.

Each of the 72 LCD buttons are capable of displaying a multiple character text string. They can also be configured with a menu structure that allows quick navigation through the systems. When a menu button is pressed, some or all of the buttons change their function and legend. Their operation is then defined by the configuration setup for this new menu. The selection of a new menu can also be configured to change the graphical display of one or both the LCD screens.

The CP-2272E is a very sophisticated advanced panel that allows you to create a very powerful and very simple interface to your entire system. It is ideal for applications where a panel design with more LCD buttons is critical based on number of sources, destinations, levels to control etc... is desired. This makes it perfect in many different environments including Production areas, Technical Director areas, "Tape" areas etc... Considering its small footprint, the CP-2272E is perfect for use in truck and mobile applications.

►Features & Benefits

- Flexible feature or menu driven configurations providing quick and simple access
- Two small high quality LCD displays which dynamically react with the panels buttons and rotary controls
- Easily reconfigured for regularly changing environments
- Fully programmable buttons
- Supports Ethernet for connection to MAGNUM Router Control System
- Comes with main and redundant power supply



►Specifications

Control:		Dimensions:	19" W x 3.5" H x 4" D. (483mm W x 89mm H x 101mm D)	EMI/RFI:	Complies with FCC Part 15 Class A regulations
Joystick:	8 Parallel contact closure TTL Levels, D9 male	Weight:	10 lbs. (4.5kg)		Complies with EU EMC directive
Ethernet:	10/100 base T, RJ45 connector	Operating Temp.:	0-40°C		
Electrical:		Compliance:			
Configuration:	Dual Redundant	Safety:	TüV listed, complies with EU safety directives		
Voltage:	Auto-ranging 100V - 240V AC, 50/60Hz		TUV Listed to CAN/CSA-C22.2 No. 62368-1:2014,		
Power:	40 Watts		ANSI/UL 62368-1:2014, EN 62368-1:2014+A11:2017, IEC 62368-1:2014		
Fuse Rating:	250V, 1A, time delay				
Physical:					

►Ordering Information

CP-2272E 2RU Advanced System Control Panel with 72 LCD button panel and dual small LCD Screens with Advanced Control for MAGNUM-Router (requires MAGNUM-Router). Includes a main and redundant power supply